

## Technical Data Sheet

Compatible with Element, Element HT & Array



### Description

Mosaic ASA has excellent mechanical properties, similar to those of ABS. This material has the added benefit of being UV stable, making it suitable for outdoor use.

#### Key Features

- ✓ UV Resistant
- ✓ High Thermal Resistance
- ✓ Durable
- ✓ Tough
- ✓ Hydrolytic Stability

#### Sample Applications

- ✓ Tool Casings
- ✓ Garden Equipment
- ✓ Marine Applications
- ✓ Outdoor Signage
- ✓ Jigs and Fixtures

### Available Colours



Black White

### Filament Specifications

Diameter	Tolerance
1.75 mm	+/- 0.05 mm

## Printing Guidelines

<b>Slicer Profile</b>	Coming soon to canvas3d.io
<b>Nozzle Temperature</b>	265°C
<b>Heated Chamber</b>	Recommended for larger geometries
<b>Build Surface</b>	Element Bed Type I, with glue stick
<b>Special Considerations</b>	N/A

## Storage/Handling Considerations

<b>Hygroscopicity</b>	Low
<b>Drying Temperature</b>	70°C
<b>Drying Time</b>	6 Hours

**Note:** When not in use, spool should be stored in a Mosaic Material Pod or inside a vacuum sealed container.

## Material Properties

<b>Property</b>	<b>Standard</b>	<b>Typical Value</b>
Density	ISO 1183	1.13 g/cc
Tensile Strength, Break	ISO 527	46.25 MPa
Tensile Modulus	ISO 527	2412 MPa
Elongation at break	ISO 527	9.51%
Heat Deflection Temp.	ISO 75 1.8 MPa	99.8°C

## Multi-Material Compatibility

### Automation

---

Same-material Automated Changeover	With Material Pod
------------------------------------	-------------------

---

### Supports

---

Same-material support	Yes
Compatible Soluble Materials	HIPS (soluble in d-limonene)
Compatible Breakaway Materials	HIPS

---

## Section 1: Identification

### Product Identification:

**Product Name:** Mosaic ASA  
**Chemical Name:** Acrylonitrile Styrene Acrylate (ASA)  
**Recommended Use:** Additive manufacturing

### Supplier Information:

Mosaic Manufacturing  
403-111 Peter Street, Toronto, Ontario, Canada M5V 2H1  
Phone 647-570-0375  
Email: [info@mosaicmfg.com](mailto:info@mosaicmfg.com)

## Section 2: Hazard(s) Identification

**Regulation (EC) NO 1272/2008:** Not classified as a dangerous product

**Physical Hazards:** None

**OSHA Regulatory Status:** This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

## Section 3: Composition/Information on Ingredients

None of the substances, named in the Candidate list art. 59 (1,10) of the REACH regulation EC no. 1907/2006 has been used in a concentration > 0,1%.

## Section 4: First-Aid Measures

**Eyes:** Flush with water. Consult a physician if symptoms persist.

**Skin Contact:** Wash with soap and water. For thermal burns from molten polymer, immediately flush with cold water. Do not attempt to remove cooled polymer from the skin. Obtain medical attention.

**Inhalation:** Leave exposed area and seek fresh air. If irritation persists seek medical attention.

**Ingestion:** Not likely due to the nature of the product. If ingested, drink plenty of water. Do not induce vomiting. Consult a physician if symptoms persist.

## Section 5: Fire-Fighting Measures

**Extinguishing Media:** Water spray, dry powder, and foam. Carbon dioxide (CO<sub>2</sub>)

Safety Precautions for Persons exposed to products of combustion should wear NIOSH approved self contained breathing apparatus and full protective equipment.

## Section 6: Accidental Release Measures

**Spill or release:** Clean up by vacuuming or sweeping to prevent falls. If molten, allow material to cool and place into an appropriate container for disposal.

## Section 7: Handling and Storage

**Precautions to be taken in handling and storage:** Store in a dry, sprinkler equipped warehouse. Product as shipped is not a combustible dust. Mechanical handling can cause the formation of dusts. To reduce the risk for dust explosion, avoid dust accumulation.

**Waste Disposal:** Dispose in accordance with applicable federal, state and local regulations.

## Section 8: Exposure Controls/Personal Protection

**Exposure Limits:** This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

**Respiratory Protection:** A NIOSH approved respirator is recommended for protection against processing polymeric fumes, or from dust generated from grinding, sanding, or sawing operations.

**Ventilation:** Local exhaust is preferred.

**Protection Gloves:** Canvas or cotton gloves are recommended.

**Eye Protection:** Safety glasses with side shields are recommended. Other: No protective equipment is needed under normal use conditions.

## Section 9: Physical and Chemical Properties

<b>State:</b>	Solid
<b>Form:</b>	Filament
<b>Color:</b>	Varies
<b>Odor:</b>	None
<b>Solubility in Water:</b>	Insoluble
<b>Specific Gravity:</b>	>1
<b>% Volatile:</b>	N/A
<b>Boiling Range:</b>	N/A
<b>Vapor Pressure (MM HG):</b>	Negligible

**Melting Point/Freezing Point:** 140 - 170 °C.

**Note:** Those physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

## Section 10: Stability and Reactivity

**Polymerization conditions to avoid:** None

**Chemical Stability:** Stable under normal conditions

**Conditions to avoid:** Incompatible materials, including strong oxidizing agents

**Hazardous decomposition byproducts:** Thermal decomposition can yield intense heat, dense smoke, phenols, hydrogen cyanide, carbon dioxide, and carbon monoxide.

## Section 11: Toxicological Information

No specific toxicological information is available.

## Section 12: Ecological Information

No specific ecological information is available.

## Section 13: Disposal Considerations

**Waste Disposal:** Waste or unused product may be discarded in accordance with state, federal, and local regulations.

## Section 14: Transport Information

**Land Transport (DOT):** Non-Regulated

**Sea Transport (IMDG):** Non-Regulated

**Air Transport (ICAO/IATA):** Non-Regulated

## Section 15: Regulatory Information

<b>TSCA:</b>	Complies
<b>EINECS/ELINCS:</b>	N/A
<b>DSL/NDSL:</b>	Complies
<b>PICCS:</b>	N/A
<b>ENCS:</b>	Complies
<b>IECSC:</b>	Complies
<b>AICS:</b>	Complies
<b>KECL:</b>	Complies

## Section 16: Other Information

Prepared by: Mosaic Manufacturing

Issued: 05/04/2023

Supersedes: N/A

This information set forth herein has been gathered from standard reference materials and/or supplier test data and is, to the best knowledge and belief of Mosaic Manufacturing, accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones which exist. Mosaic Manufacturing makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein combination with any other material or process, and assumes no responsibility therefore.